

**WARNING — FOR CONTINUED PROTECTION AGAINST FIRE HAZARD REPLACE ONLY WITH A FUSE OF THE SAME TYPE AND HAVING THE SAME ELECTRICAL RATING.**

**F9  
F9A**

DISPLAY FILAMENT  
1 AMP NORMAL-BLO  
32 V

**F6**

PLAYFIELD ILLUMINATION  
5 AMP SLO-BLO  
250 V

**F5**

CONTROLLED LAMPS  
8 AMP SLO-BLO  
250 V

**F4**

SOLENOIDS (+24V DC)  
8 AMP SLO-BLO  
250 V

**F3**

DISPLAY (32V AC)  
0.25 AMP SLO-BLO  
250 V

**F2**

POWER SUPPLY (A2)  
6.25 AMP SLO-BLO  
250 V

**F1**

SOUND POWER SUPPLY (A5)  
0.50 AMP NORMAL-BLO  
32 V

PRIMARY POWER  
5 AMP SLO-BLO/115 VAC  
2.5 AMP SLO-BLO/230 VAC

**F8**

LIGHTBOX ILLUMINATION  
0.50 AMP  
250V. SLO-BLO

**F7**

A-25470

**WARNING — FOR CONTINUED PROTECTION AGAINST FIRE HAZARD REPLACE ONLY WITH A FUSE OF THE SAME TYPE AND HAVING THE SAME ELECTRICAL RATING.**

**F6**

PLAYFIELD ILLUMINATION  
5 AMP  
250V. SLO-BLO

**F5**

CONTROLLED LAMPS  
10 AMP  
250V. SLO-BLO

**F4**

SOLENOIDS (+24V DC)  
8 AMP  
250V. SLO-BLO

**F3**

DISPLAY (32V AC)  
0.25 AMP  
250V. SLO-BLO

**F2**

POWER SUPPLY (A2)  
6.25 AMP  
250 V. SLO-BLO

**F1**

SOUND POWER SUPPLY (A5)  
0.50 AMP  
250V. NORMAL-BLO

PRIMARY POWER  
5 AMP SLO-BLO/115 VAC  
2.5 AMP SLO-BLO/230 VAC

**F8**

LIGHTBOX ILLUMINATION  
0.50 AMP  
250V. SLO-BLO

**F7**

A-25029

**WARNING — FOR CONTINUED PROTECTION AGAINST FIRE HAZARD REPLACE ONLY WITH A FUSE OF THE SAME TYPE AND HAVING THE SAME ELECTRICAL RATING.**

**F15**

SOUND SPEECH (WHEN USED)

**F7**

LIGHTBOX ILLUMINATION  
10 AMP.  
250V. SLO-BLO

**F6**

PLAYFIELD ILLUMINATION  
8 AMP.  
250V. SLO-BLO

**F5**

CONTROLLED LAMPS  
10 AMP.  
250V. SLO-BLO

**F4**

SOLENOIDS (+24V DC)  
8 AMP.  
250V. SLO-BLO

**F3**

DISPLAY (60V AC)  
0.25 AMP.  
250V. SLO-BLO

**F2**

POWER SUPPLY (A2)  
5 AMP.  
250 V. SLO-BLO

**F1**

SOUND POWER SUPPLY (A6)  
0.50 AMP.  
250V. NORMAL-BLO

**F8**

PRIMARY POWER  
5 AMP SLO-BLO/115 VAC  
2.5 AMP SLO-BLO/230 VAC

A-24421

ATTENTION — POUR ASSURER LA PROTECTION CONTRE LES SURTENSIONS NE REMPLACER LES FUSIBLES QUE PAR DES FUSIBLES D'ORIGINE AYANT LES MEMES CARACTERISTIQUES ELECTRIQUE.

**F9** FILAMENT DE L’AFFICHEUR  
**F9A** 1 AMP NORMAL BLO  
250V

**F6** ILLUMINATION DU PLATEAU  
5 AMP SLO-BLO  
250V

**F5** LAMPES CONTROLLEES  
8 AMP SLO-BLO  
250V

**F4** BOBINES  
8 AMP SLO-BLO  
250V

**F3** AFFICHEURS  
0.25 AMP SLO-BLO  
250V

**F2** ALIMENTATION  
6.25 AMP SLO-BLO  
250V

**F1** ALIMENTATION PLAQUE SON  
0.50 AMP NORMAL-BLO  
250V

FUSIBLE PRIMAIRE  
5 AMP SLO-BLO/115 VAC  
2.5 AMP SLO-BLO/230 VAC

**F8**

ILLUMINATION DU FRONTON  
.50 AMP SLO-BLO  
250 V

**F7**

A-25471

WARNING — FOR CONTINUED PROTECTION AGAINST FIRE HAZARD REPLACE ONLY WITH A FUSE OF THE SAME TYPE AND HAVING THE SAME ELECTRICAL RATING.

**F6** PLAYFIELD ILLUMINATION  
6.25 AMP  
250V. SLO-BLO

**F5** CONTROLLED LAMPS  
8 AMP  
250V. SLO-BLO

**F4** SOLENOIDS (+24V DC)  
8 AMP  
250V. SLO-BLO

**F3** DISPLAY (32V AC)  
0.25 AMP  
250V. SLO-BLO

**F2** POWER SUPPLY (A2)  
6.25 AMP  
250 V. SLO-BLO

**F1** SOUND POWER SUPPLY (A5)  
0.50 AMP  
250V. NORMAL-BLO

PRIMARY POWER  
5 AMP SLO-BLO/115 VAC  
2.5 AMP SLO-BLO/230 VAC

**F8**

LIGHTBOX ILLUMINATION  
0.50 AMP  
250V. SLO-BLO

**F7**

A-25096

WARNING — FOR CONTINUED PROTECTION AGAINST FIRE HAZARD REPLACE ONLY WITH A FUSE OF THE SAME TYPE AND HAVING THE SAME ELECTRICAL RATING.

**F7** 10 AMP  
250V. SLO-BLO

**F6** 8 AMP  
250V. SLO-BLO

**F5** 7.5 AMP  
250V. SLO-BLO

**F4** 8 AMP  
250V. SLO-BLO

**F3** 0.25 AMP  
250V. SLO-BLO

**F2** 5 AMP  
250 V. SLO-BLO

**F1** 0.50 AMP.  
250V. NORMAL-BLO

**F8**

5 AMP SLO-BLO/115 VAC  
2.5 AMP SLO-BLO/230 VAC

A.S.

LIGHTBOX ILLUMINATION  
0.50 AMP SLO-BLO  
250 V

PRIMARY POWER  
5 AMP SLO-BLO/115 VAC  
2.5 AMP SLO-BLO/230 VAC

**F7**

**F8**

**F1** SOUND POWER SUPPLY (A5)  
0.50 AMP NORMAL-BLO  
32 V

**F2** POWER SUPPLY (A2)  
6.25 AMP SLO-BLO  
250 V

**F3** DISPLAYS (32V AC)  
0.25 AMP SLO-BLO  
250 V

**F4** SOLENOIDS (+24V DC)  
8 AMP SLO-BLO  
250 V

**F5** CONTROLLED LAMPS  
10 AMP SLO-BLO  
32 V

**F6** PLAYFIELD ILLUMINATION  
5 AMP SLO-BLO  
250 V

**F9** DISPLAY FILAMENT  
1 AMP NORMAL BLO  
32 V

**F9A**

**WARNING** - FOR CONTINUED PROTECTION  
AGAINST FIRE HAZARD REPLACE ONLY WITH A  
FUSE OF THE SAME TYPE AND HAVING THE SAME  
ELECTRICAL RATING.

**WARNING** — FOR CONTINUED PROTEC-  
TION AGAINST FIRE HAZARD REPLACE ONLY  
WITH A FUSE OF THE SAME TYPE AND HAVING  
THE SAME ELECTRICAL RATING.

**F15**

NOT USED

**F7**

10 AMP  
250V. SLO-BLO

**F6**

8 AMP  
250V. SLO-BLO

**F5**

10 AMP  
250V. SLO-BLO

**F4**

8 AMP  
250V. SLO-BLO

**F3**

0.25 AMP  
250V. SLO-BLO

**F2**

5 AMP  
250 V. SLO-BLO

**F1**

0.50 AMP  
250V. NORMAL-BLO

**F8**

5 AMP SLO-BLO/115 VAC  
2.5 AMP SLO-BLO/230 VAC

**WARNING** — FOR CONTINUED PROTECTION  
AGAINST FIRE HAZARD REPLACE ONLY WITH A  
FUSE OF THE SAME TYPE AND HAVING THE SAME  
ELECTRICAL RATING.

**F15**

SOUND SPEECH (WHEN USED)

**F7**

LIGHTBOX ILLUMINATION  
8 AMP.  
250V. SLO-BLO

**F6**

PLAYFIELD ILLUMINATION  
8 AMP.  
250V. SLO-BLO

**F5**

CONTROLLED LAMPS  
10 AMP.  
250V. NORMAL-BLO

**F4**

SOLENOIDS (+24V DC)  
8 AMP.  
250V. SLO-BLO

**F3**

DISPLAY (32V AC)  
0.25 AMP.  
250V. SLO-BLO

**F2**

POWER SUPPLY (A2)  
5 AMP.  
250 V. SLO-BLO

**F1**

SOUND POWER SUPPLY (A6)  
0.50 AMP.  
250V. NORMAL-BLO

**F8**

PRIMARY POWER  
5 AMP SLO-BLO/115 VAC  
2.5 AMP SLO-BLO/230 VAC

23950

24174-1

A-24483

Fonts used: News Gothic Std.

**Cards status:**

A-25470 Fuse card confirmed (Victory).

A-24421 Fuse card confirmed (Ice Fever).

A-25029 Fuse card confirmed (Hollywood Heat).

A-25096 Fuse card confirmed (Goldwings).

A-25471 French fuse card confirmed (Victory).

Fuse card labelled as "A.S." needed to verify (Alien Star).

A-25950 Fuse card confirmed (Hot Shots).

A-24174-1 Fuse card confirmed (Touchdown).

A-24483 Fuse card confirmed (Chicago Cubs).

If you have any other information about these cards, please send a readable picture or scan to me.

Enjoy and have fun,

Peter

[www.inkochnito.nl](http://www.inkochnito.nl)

If you like my work, please send me a donation via PayPal.